


| | | |
|---|--|---------------|
|  | Quality system | ETPA: 080PCPG |
| Date: 22/12/14 | FINISHED PRODUCT SPECIFICATIONS | Version: 1 |
| DENOMINATION: PROFILE DIN TYPE "C" | | Page: 1/1 |

TECHNICAL SPECIFICATIONS: (specifications according standard EN-60715:2001):

MATERIAL (Annex A of Standard)



- Cold laminated carbon steel.
- Bright surface finish
- Tensile strength of 320 N/mm² and 420 N/mm²
- Elongation at least 30%
- Bending test of 180 horizontal and transverse to the rolling direction.

COATING:

- Pre-galvanized with minimum coat of 6 micron (recommended 10 microns minimum)

DIMENSIONS / REFERENCE TABLE:

- Strips 2m.
- Dimensions:

| REFERENCE | DESCRIPTION |
|--|---|
| 080PCPG201 PROFILE TYPE C 20X10 PERFORATED PRE GALVANIZED |  <p>A-A' SECTION</p> <p>dimensions in mm.</p> |
| 080PCPG402 PROFILE TYPE C 40X20 PERFORATED PRE GALVANIZED |  <p>A-A' SECTION</p> <p>dimensions in mm.</p> |

| | DEPARTMENT | RESPONSIBLE | DATE | FIRM |
|-------------------------------|--------------------|--------------|------------|--------|
| PREPARED REVISED AND APPROVED | TECHNICAL DEPARTT. | C.Valdeperas | 22/12/2014 | Carles |