	QUALITY SYSTEM	ETPA: 090MANGUN
Date: 04/01/16	TECHNICAL SPECIFICATION	Versión: 1
PRODUCT: <b>COUPLING FOR EARTH RODS</b>		Page: 1/1

## COUPLING FOR EARTH RODS

### TECHNICAL SPECIFICATIONS

- Material: CZ121 Pb3 / CuZn39Pb3.


The material must be compatible with the material of the earth rod and according to the standard UNE-EN-1982, UNE-EN-12164 or UNE-EN 12165.

- The threaded couplings must be cylindrical and must be threaded along its entire length.
- Minimum outside diameter of 22,0mm. for earth rod with M16x2 thread
- Minimum outside diameter of 27.0mm. for earth rod threaded M20x2,5
- coupling length L = 70 mm + 5 / -0mm.

### REFERENCE TABLE

Coupling	Inside screw	Outside diámetro	Lenght	Reference ARMENGOL	Reference AXIS
M16	M16x2	22,0 mm.	70mm +5/-0mm.	0502MRPMM016	BRASSCOUPM16
M20	M20x2,5	27,0 mm.	70mm +5/-0mm.	0502MRPMM020	BRASSCOUPM20

### SKETCH:



### PACKAGING:

- In bulk

	DEPARTMENT	RESPONSIBLE	DATE	SIGNATURE
ELABORATED	TECHNICAL DEP.	Carles Valldeperas	04/01/2016	Carles